

JIGA JIGA Paint

Exterior Satin

Product base code: JJES



Product description

Jiga Jiga Paint Exterior Satin is a 100% acrylic self-priming exterior paint suitable for a wide range of exterior surfaces. It delivers fantastic coverage, excellent application properties and outstanding durability. The premium exterior paint has a 12-Year performance guarantee against blistering, peeling and flaking.

Key features & benefits

Self-priming	Apply directly onto most surfaces
Excellent UV resistance	Protection against deterioration
12-Year Guarantee* Protection against blistering, peeling and flaking.	



Where to Use

Substrates:	Brick, Concrete, Cement-Sheet, Masonry, Colorbond®, Metal (ferrous), Redner, uPVC, Timber-Exterior, Timber-Plywood, Timber-Weatherboard, Zinc treated steel.
Exterior:	Cladding, Eaves, Fascias, Gutters and Downpipes, Outdoor furniture, Pergolas, Weatherboards, Walls
	Not recommended for use on timber decking and walk-on surfaces.

Product properties

Colour(s)	White, Ultra Deep Tint, Extra Dark Tint
Gloss level	60° 29 – 34 85° 48 - 54
Clean-up	Water
Dry time – touch dry	20 minutes
Dry time - recoat	2 hours
Coverage per litre	Up to 16m ² /L depending upon surface porosity, profile and method of application.
Sizes	4 L, 10 L
VOC	56 g/L
Certifications & approvals	
Volume solids	39%
Film build wet	63µm
Film build dry	24µm

Precautions

- Do NOT apply if the ambient temperature is less than 10°C or greater than 35°C or if conditions will drop below 10°C during the drying period. Under warmer conditions refer to thinning advice.
- All times quoted assume ambient conditions of 25°C and 50% relative humidity. At cooler temperature or higher humidity, drying times will be extended.
- Do NOT apply if rain or dew is expected within 24 hours of application.
- Provide adequate ventilation during application and the drying period.
- Do NOT paint in direct sunlight.
- Please consider the use of dark colours on exposed building materials, and follow the manufacturer's light reflectance value (LRV) recommendation.
- For bright and deep colours, to ensure colour accuracy and opacity, apply the specified tinted undercoat prior to the application of the topcoat(s).
- Under normal conditions, the coating may require up to seven days curing to develop hardness and properties.
- If more than one can is required for the final coat, mix all cans together prior to commencing.
- **Please check the colour for accuracy before application.**

Surface Preparation

Preparation: All surfaces must be clean, bare, dry and free of wax, grease and other surface contaminants. Fill any cracks, nail holes or imperfections with the appropriate filler. Sand smooth and dust down. If mould is present, treat the surface with a mould remover to effectively eliminate the mould spores. All traces of mould must be removed prior to painting.

Previously painted surfaces	Conduct an adhesion test ¹ , followed by a compatibility test ² . Scrape all loose flaking paint. Sand surface smooth to a dull finish and remove all dust. Apply one coat of Haymes Paint Ultracover, however, for surfaces in sound condition, no primer or undercoat is required.
Timber	Weathered or greyed timber should be sanded to the original timber surface. Apply one coat of Haymes Paint Ultralock for tannin-rich timbers. For pre-primed timbers, please refer to the manufacturer's painting specification ³ .
Brick, fibre-cement sheeting	Clean the surface using a pressure washer and allow to dry. Apply one coat of Jiga Jiga Acrylic Sealer Undercoat.
Cement render, concrete, masonry AAC	New concrete must be left to cure for 28 days before painting. Clean the surface using a pressure washer and allow to dry. Ensure concrete surfaces are free from any bond breakers, formwork release agents and efflorescence. Apply one coat of Jiga Jiga Acrylic Sealer Undercoat.
Pre-primed cement sheeting (e.g., Scyon Matrix)	Surface must be free of dust and grease, or other contaminants. Conduct an adhesion test ¹ . Apply one coat of Haymes Paint Ultracover.
Pre-cast concrete, tilt-up	Mould release agents must be fully removed prior to painting. Clean the surface using Haymes Paint Rendertex Tilt Panel Prep, then rinse with a hot pressure wash. Check the surface in several areas for water beading. If water beads cleaning must be repeated until no water beading occurs. Apply one coat of Haymes Paint Rendertex Masonry Sealer.
uPVC	Wash the surface with a sugar soap and rinse with clean water. Scuff the surface with sandpaper and remove dust.

¹ To check the adhesion of an existing coating, cut an 'X' lightly into the coating and firmly apply adhesive tape across the cut and then remove tape. If the tape removes the existing coating, remove all previous coatings before painting.

² Test for compatibility with a previous coating by sanding and cleaning a small inconspicuous area. Apply 1 coat of the desired topcoat and allow to dry. After 24 hours conduct an adhesion test. If the tape removes the coating, remove all previous coatings before painting. It is recommended to conduct the compatibility test in several areas.

³ Some primers used on pre-primed timber are of low quality. Unless a painting specification is supplied by the timber manufacturer, the timber must be sanded back to bare timber before coating.

Surface Preparation (continued)	
Colorbond®	Ensure weathered Colorbond® surfaces are clean and free of salts or other deposits. Wash new Colorbond® surfaces with a non-metallic scourer and sugar soap.
Galvanised iron	Thoroughly degrease new surfaces with a non-metallic scourer. Wash degreased and weathered surfaces using sugar soap. Rinse with clean water. Apply one coat of Haymes Paint Ultracover. Structural Galvanised iron must be abraded and primed with a metal or etch primer.
Metal (ferrous), steel, wrought iron	Remove all loose rust by wire brushing, scraping or sanding. Apply one coat of Haymes Paint Rustlock Primer or Ultraprime or two coats of Ultraprime with a water-based topcoat. For harsh exposure environments and areas within 3 km of the coast apply two coats of Haymes Paint Ultraprime or Rustlock Primer. For longer-lasting corrosion protection on new surfaces, we recommend the Rustlock metal protection system.
Zinc treated steel, Zincaneal®, Galvanneal, Duragal®	Ensure Zinc treated surfaces are clean and free of oil, salts or other deposits. Remove oil using a solvent degreaser, then wash new surfaces with a non-metallic scourer and sugar soap.
Zincalume®	Remove oil using a solvent degreaser, then wash with sugar soap using a mop or soft bristle brush, rinse with clean water.
IMPORTANT: You must consult the installation guide of the construction product you are using for information on coatings and finishing systems to determine product suitability prior to commencing work. For further information and product specification consult a Jiga Jiga Paint representative on contact@jigajigapaint.com.au .	

Application

- Stir thoroughly before and during application using a broad flat stirrer.
- Apply a minimum of two coats; or three coats when applied to bare timber.
- Application methods:
- Brush: Use a quality synthetic brush.
- Roller: Smooth to semi-smooth surfaces use 11-12mm nap length.
- Semi-smooth to rough surfaces use 14-18mm nap length.
- Rough or uneven surfaces use 20-22mm nap length.
- Spray: For airless spray use a 15-17 thou @ 2000-2500 psi.
- The use of low-pressure tips will require a lower pressure range.

Thinning

Thinning is not recommended unless spraying; add up to 100mL clean water per litre of paint to achieve acceptable atomisation. Up to 50mL of clean water can be added per litre of paint to ease application under very warm conditions. Thinning may necessitate additional coats to achieve required film builds.

Care and Maintenance

Regular cleaning of the surface will assist in removing dirt, dust and contaminants, which will result in a longer coating life.

Storage

Containers must be secured and stored upright during transit. Protect from extremes of temperature. Store in a cool, dry, well-ventilated place and out of direct sunlight. Check regularly for leaks.

*Warranty

Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss or damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure.

We provide the following in relation to our Satin product. The benefits of this warranty are in addition to any rights and remedies imposed by Australian State and Federal legislation that cannot be excluded. Nothing in this warranty excludes, restricts or modifies any State or Federal legislation applicable to the supply of goods which cannot be so excluded, restricted or modified.

GUARANTEE

We warrant that, subject to the exclusions and limitations below; the Product will be free from peeling, flaking and blistering (Defects) for 12 years. The warranty period commences on the date of sale of the Product.

If a Defect appears in the Product before the end of the warranty period and we find the Product to be defective, we will provide, free of charge, sufficient paint to rectify the area affected by the Defect. We reserve the right to provide paint of similar quality, grade and composition where an identical paint is not available. We reserve the right to change or discontinue our product ranges at any time without notice and without liability.

EXCLUSIONS

This 12-year warranty does not apply in the following circumstances:

- (a) where Jiga Jiga Paint cannot establish a Defect with the Product;
- (b) where there is damage to the surface prior to the application of the Product;
- (c) where the Product is not applied in accordance with the preparation instructions or Product Data Sheet;
- (d) where surface preparation is not completed in line with instructions;
- (e) where the Product has been adulterated in any way;
- (f) where there has been a breakdown of previous coatings on the surface to which the Product has been applied.

HOW TO CLAIM

Any claims for warranty should be made with proof of purchase and full details of the alleged Defect, to the address listed below **within 30 days** of the Defect occurring. Photographs of the Defect must be provided to Jiga Jiga Paint for assessment, and a site visit by a Jiga Jiga Paint representative may be requested. The cost of delivery of paint to rectify any Defect will be the responsibility of Jiga Jiga Paint on the determination of a valid warranty claim by Jiga Jiga Paint.

LIMITATIONS

We make no express warranties, or representations other than as set out in this Warranty. The provision of sufficient paint to rectify the area affected by the Defect is the absolute limit of our liability under this Warranty.

CONTACT

Jiga Jiga Paint Email: contact@jigajigapaint.com.au

Safety & First Aid

Keep out of reach of children. Avoid contact with skin and eyes. Wear suitable, protective clothing, eye protection and impervious gloves when mixing and using. If swallowed, drink plenty of water and seek medical advice. Contact a doctor or Poisons Information Centre (Phone 13 11 26). If skin contact occurs, remove contaminated clothing and wash skin thoroughly with soap and water. If irritation develops or persists seek medical advice. In case of eye contact, hold eyes open and flush with running water for at least 15 minutes and seek medical advice.

CONTAINS ISOTHIAZOLINONES. REPEATED EXPOSURE MAY CAUSE SENSITISATION.

Protect our environment

DO NOT pour any leftover product down the drain. Retain in a marked sealed container for future use or disposal via special chemical waste collection programs such as Paintback®. Check on the Paintback® website www.paintback.com.au for details of the closest depot. Dried empty containers can be recycled and should be disposed of via recycling facilities.

Disclaimer

The information provided is correct at the time of preparation; however, it is the responsibility of those using this information to check that it is current before specifying, recommending, or using product contained in this information. Because use conditions and applicable laws may differ from one location to another and may change with time, those using this information are responsible for determining whether products and the information in this document are appropriate for their use and for ensuring that workplace and disposal practices comply with applicable laws and other government enactments. Jiga Jiga Paint assumes no obligation or liability for the information in this document. No express warranties are given except for any applicable written warranties specifically provided by Jiga Jiga Paint. All implied warranties including those of merchantability and fitness for a particular purpose are expressly excluded. Document valid unless superseded.

Date of Preparation 22/06/2022